


65172LF▲



Submitted Model No.: _____

Specific Features: _____



BRIZO®

LAVATORY FAUCETS

- Loki® Bath Collection
- Two Handle Deck Mount
- Single Hole Mount
- Swivel Spout

STANDARD SPECIFICATIONS:

- Two handle lavatory faucet for concealed mounting on one hole applications.
- 5 13/16" (148 mm) long spout.
- Recommended 1 3/8" hole size.
- Spout swivels 120°.
- Model has metal drain with pop-up type fitting with plated flange and stopper.
- Accommodates up to 3 5/16" deck thickness.
- Control mechanism shall be of the rotating ceramic cylinder type.
- Handles slide on and off.
- Maximum flow rate 1.5 gpm @ 60 PSI, 5.7L/Min.


WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense
- Verified compliant with .25% weighted average Pb content regulations.



▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.

Delta Faucet Company

55 E. 111th Street, Indianapolis, Indiana 46280
 395 Matheson Blvd. E., Mississauga, ON L4Z 2H2
 © 2009 Masco Corporation of Indiana